

Sony VPL-GTZ380 - SXRD projector - no lens - 3D



Not in stock

SKU	VPL-GTZ380
Product Description:	Sony VPL-GTZ380 - SXRD projector - no lens - 3D
Device Type:	SXRD projector - 4K
3D Capable:	Yes
Brightness:	10000 lumens
Brightness (Colour):	10000 lumens
Contrast Ratio:	16000:1
Resolution:	4096 x 2160



General

Device Type:	SXRD projector - 4K
3D Capable:	Yes
Networking:	Ethernet

Projector

Brightness:	10000 lumens
Brightness (Colour):	10000 lumens
Contrast Ratio:	16000:1
Resolution:	4K - 4096 x 2160
Display Format:	26,542,080 pixels (4096 x 2160) x 3
Max Sync Rate (V x H):	120 Hz
Bulb type:	Laser/phosphor
OSD Languages:	Multilingual
Features:	High Dynamic Range (HDR), 100% DCI-P3 colour gamut

Lens

Type:	No lens
-------	---------

Video Input

Video Interfaces:	HDMI, DisplayPort
Video Modes:	1080/24p, 1080/50p, 1080/60p, 2160/50p, 2160/60p, 2160/100p, 2160/120p, 1080/120p, 1080/100p

Environmental Parameters

Min Operating Temperature:	5 °C
Max Operating Temperature:	40 °C
Humidity Range Operating:	20 - 80% (non-condensing)
Sound Emission:	33 dB
Sound Emission (Economic Mode):	39 dB

Dimensions & Weight

Width:	56 cm
Depth:	76 cm
Height:	26.2 cm
Weight:	51 kg

Power

Power Source:	AC
Voltage Required:	AC 120/230 V (50/60 Hz)
Power Consumption Operational:	2 kW
Power Consumption Stand by:	0.5 Watt

Miscellaneous

Included Accessories:	2 x AA batteries, remote control
Compliant Standards:	HDCP 2.3

Expansion / Connectivity

Interfaces:	2 x HDMI input - 19 pin HDMI Type A ; 2 x DisplayPort input - 20 pin DisplayPort ; 2 x remote control - mini-phone 3.5 mm ; 1 x serial RS-232C - 9 pin D-Sub (DB-9) (management) ; 1 x network - RJ-45 ; 1 x remote control input - mini-phone 3.5 mm ; 1 x remote control output - mini-phone 3.5 mm ; 1 x 3D Sync in/out - 3 PIN mini-DIN ; 1 x USB - 4 pin USB Type A
-------------	--