

StarTech.com 1 Port Industrial RS-232 / 422 / 485 Serial to IP Ethernet Wireless Device Server with Redundant Power - device server - Wi-Fi



06-06-2024

SKU	NETRS232485W
Product Description:	StarTech.com 1 Port Industrial RS-232 / 422 / 485 Serial to IP Ethernet Wireless Device Server with Redundant Power - device server - Wi-Fi
Device Type:	Device server
Form Factor:	External
Data Link Protocol:	Ethernet, Fast Ethernet, RS-232, IEEE 802.11b, IEEE 802.11g, RS-422, RS-485
Frequency Band:	2.4 GHz
OS Required:	Microsoft Windows Server 2003, Microsoft Windows Server 2008 R2, Microsoft Windows Server 2012, Microsoft Windows Vista / XP / 7 / 8, Microsoft Windows Server 2016
Power:	DC 12 - 48 V



General

Device Type:	Device server
Width:	2.9 cm
Depth:	7.2 cm
Height:	12.3 cm
Weight:	346 g
Enclosure Colour:	Black

Networking

Form Factor:	External
Connectivity Technology:	Wireless, wired
Data Link Protocol:	Ethernet, Fast Ethernet, RS-232, IEEE 802.11b, IEEE 802.11g, RS-422, RS-485
Network / Transport Protocol:	TCP/IP, UDP/IP, ICMP/IP, PPPoE, SMTP, BOOTP, DHCP, DNS, DDNS
Remote Management Protocol:	SNMP 1, SNMP 2c, HTTPS, SSH
Frequency Band:	2.4 GHz
Status Indicators:	Power, transmit, receive, WLAN, LAN
Features:	Flow control, auto-uplink (auto MDI/MDI-X)
Compliant Standards:	IEEE 802.3, IEEE 802.3u, IEEE 802.11b, IEEE 802.11g

Environmental Parameters

Min Operating Temperature:	-10 °C
Max Operating Temperature:	65 °C
Humidity Range Operating:	5 - 95% (non-condensing)

Manufacturer Warranty

Service & Support:	Limited warranty - 3 years
--------------------	----------------------------

Software / System Requirements

Software Included:	Drivers & Utilities
OS Required:	Microsoft Windows Server 2003, Microsoft Windows Server 2008 R2, Microsoft Windows Server 2012, Microsoft Windows Vista / XP / 7 / 8, Microsoft Windows Server 2016

Power

Power Device:	Internal power supply
Voltage Required:	DC 12 - 48 V

Miscellaneous

MTBF:	29,268 hour(s)
Compliant Standards:	FCC, RoHS

Expansion / Connectivity

Interfaces:	1 x RS-232/422/485 - DB-9 1 x 100Base-TX - RJ-45 1 x aerial - RP-SMA
-------------	--

Aerial

Antenna:	External detachable
Antenna Qty:	1
Gain Level:	2 dBi

