

StarTech.com 2 Port Serial-to-IP Ethernet Device Server - RS232 - Metal and Mountable - Serial Device Server - RS232 Serial-Over-IP (NETRS2322P) - device server



Not in stock

SKU	NETRS2322P
Product Description:	StarTech.com 2 Port Serial-to-IP Ethernet Device Server - RS232 - Metal and Mountable - Serial Device Server - RS232 Serial-Over-IP (NETRS2322P) - device server
Device Type:	Device server
Form Factor:	In-wall mountable
Localisation:	Australia, North America, United Kingdom, Europe
Ports Qty:	2
Data Link Protocol:	Ethernet, Fast Ethernet, RS-232
Included Accessories:	Power terminal block



General

Device Type:	Device server
Width:	8 cm
Depth:	11.3 cm
Height:	2.5 cm
Weight:	310 g
Enclosure Colour:	Black
Localisation:	Australia, North America, United Kingdom, Europe

Networking

Form Factor:	In-wall mountable
Ports Qty:	2
Connectivity Technology:	Wired
Data Transfer Rate:	460.8 Kbps
Data Link Protocol:	Ethernet, Fast Ethernet, RS-232
Network / Transport Protocol:	TCP/IP, UDP/IP, ICMP/IP, BOOTP, DHCP
Remote Management Protocol:	Telnet
Status Indicators:	Status, LAN, link/activity

Features:	Full duplex capability, auto-negotiation, auto-uplink (auto MDI/MDI-X), 15 KV Electrostatic Discharge Protection, reset button, 8 KV Contact Electrostatic Discharge Protection
Compliant Standards:	IEEE 802.3, IEEE 802.3u

Environmental Parameters

Min Operating Temperature:	0 °C
Max Operating Temperature:	85 °C

Manufacturer Warranty

Service & Support:	Limited warranty - 2 years
--------------------	----------------------------

Software / System Requirements

Software Included:	Drivers & Utilities, Virtual COM software (Windows only)
OS Required:	Apple MacOS, Linux, Microsoft Windows Server 2008 R2, Microsoft Windows Server 2012, Microsoft Windows Vista / 7 / 8 / 8.1 / 10, Microsoft Windows Server 2016, Microsoft Windows Server 2019

Power

Power Device:	External power adapter
Power Redundancy:	Yes
Voltage Required:	AC 120/230 V / DC 9 - 36 V

Miscellaneous

Included Accessories:	Power terminal block
Compliant Standards:	FCC, RoHS, WEEE, RCM

Expansion / Connectivity

Interfaces:	2 x RS-232 - DB-9 ; 1 x 100Base-TX - RJ-45
-------------	--