

StarTech.com 4 Port Industrial RS-232 / 422 / 485 Serial to IP Ethernet Device Server - PoE-Powered - 2x 10/100Mbps Ports - Serial over IP (NETRS42348PD) - device server



Not in stock

SKU	NETRS42348PD
Product Description:	StarTech.com 4 Port Industrial RS-232 / 422 / 485 Serial to IP Ethernet Device Server - PoE-Powered - 2x 10/100Mbps Ports - Serial over IP (NETRS42348PD) - device server
Device Type:	Device server
Form Factor:	External
Ports Qty:	4
Data Link Protocol:	Ethernet, Fast Ethernet, RS-232, RS-422, RS-485
OS Required:	Microsoft Windows Server 2003, Microsoft Windows Server 2008 R2, Microsoft Windows Server 2012, Microsoft Windows XP / Vista / 7 / 8 / 8.1 / 10, Microsoft Windows Server 2016, Microsoft Windows Server 2019
Power Over Ethernet (PoE) Supported:	PoE

General

Device Type:	Device server
Width:	10.6 cm
Depth:	5.2 cm
Height:	14.4 cm
Weight:	0.7 kg
Enclosure Colour:	Black

Networking

Form Factor:	External
Ports Qty:	4
Connectivity Technology:	Wired
Data Transfer Rate:	460.8 Kbps
Data Link Protocol:	Ethernet, Fast Ethernet, RS-232, RS-422, RS-485
Network / Transport Protocol:	TCP/IP, UDP/IP, ICMP/IP, PPPoE, SMTP, BOOTP, DHCP, DNS, DDNS
Remote Management Protocol:	SNMP 1, SNMP 2c, SSH
Status Indicators:	Port status, power, fail, PoE
Features:	Flow control, auto-uplink (auto MDI/MDI-X)
Encryption Algorithm:	128-bit SSL
Authentication Method:	Secure Shell (SSH)
Compliant Standards:	IEEE 802.3, IEEE 802.3u, IEEE 802.3af

Compatibility Information

Designed For: P/N: POEINJ4G, UPOESPLT1G

Environmental Parameters

Min Operating Temperature:	-10 °C
Max Operating Temperature:	70 °C
Humidity Range Operating:	5 - 95% (non-condensing)

Manufacturer Warranty

Service & Support: Limited warranty - 5 years

Software / System Requirements

Software Included:	Drivers & Utilities
OS Required:	Microsoft Windows Server 2003, Microsoft Windows Server 2008 R2, Microsoft Windows Server 2012, Microsoft Windows XP / Vista / 7 / 8 / 8.1 / 10, Microsoft Windows Server 2016, Microsoft Windows Server 2019

Power

Power Over Ethernet (PoE) Supported: PoE

Miscellaneous

MTBF:	569,972 hour(s)
Compliant Standards:	FCC, RoHS

Expansion / Connectivity

Interfaces: 4 x RS-232/422/485 - DB-9 | 2 x 100Base-TX - RJ-45