

StarTech.com 6 Port Unmanaged Industrial Gigabit Ethernet Switch w/ 4 PoE+ Ports & Voltage Regulation - DIN Rail/Wall Mountable PoE Switch (IES61002POE) - switch - 6 ports - unmanaged



Not in stock

SKU	IES61002POE
Product Description:	StarTech.com 6 Port Unmanaged Industrial Gigabit Ethernet Switch w/ 4 PoE+ Ports & Voltage Regulation - DIN Rail/Wall Mountable PoE Switch (IES61002POE) - switch - 6 ports - unmanaged
Device Type:	Switch - 6 ports - unmanaged
Subtype:	Gigabit Ethernet
Ports:	4 x 10/100/1000 (PoE+) + 2 x 10/100/1000
Power Over Ethernet (PoE):	PoE+
Features:	Auto-uplink (auto MDI/MDI-X), store and forward, full duplex mode
Compliant Standards:	IEEE 802.3, IEEE 802.3u, IEEE 802.3z, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3x, IEEE 802.3at



General

Device Type: Switch - 6 ports - unmanaged

Enclosure Type: DIN rail mountable, wall-mountable

Subtype: Gigabit Ethernet

Ports: 4 x 10/100/1000 (PoE+) + 2 x 10/100/1000

Power Over Ethernet (PoE): PoE+

Features: Auto-uplink (auto MDI/MDI-X), store and forward, full duplex mode

Compliant Standards: IEEE 802.3, IEEE 802.3u, IEEE 802.3z, IEEE 802.3ab, IEEE 802.3af, IEEE 802.3x, IEEE 802.3at

Status Indicators: Port transmission speed, power, fail, PoE, link/activity

Expansion / Connectivity

Interfaces: 4 x 1000Base-T RJ-45 PoE+ - 30 W | 2 x 1000Base-T RJ-45

Compatibility Information

Designed For: P/N: POEEXT1GAT, POEEXT2GAT

Environmental Parameters

Min Operating Temperature: -40 °C

Max Operating Temperature: 75 °C

Humidity Range Operating: 5 - 95% (non-condensing)

Min Storage Temperature: -50 °C

Max Storage Temperature: 85 °C

Manufacturer Warranty

Service & Support: Limited warranty - 2 years

Dimensions & Weight

Width: 6.3 cm

Depth: 10.6 cm

Height: 13.5 cm

Weight: 840 g

Miscellaneous

Colour: Black

MTBF: 296,517 hour(s)

Compliant Standards: EN 61000-4-4, EN 61000-4-2, EN 61000-4-3, EN 61000-4-6, EN 61000-4-5, FCC, EN 61000-6-2, RoHS, EN 61000-4-8, UL 60950-1, EN 61000-6-4, IEC 60068-2-27, IEC 60068-2-32, IEC 60068-2-6, EN 50121-4, IP30

Power

Power Device: Internal power supply

Voltage Required: DC 24/48 V

Power Consumption Operational: 143 Watt



