

StarTech.com Multimode (MM) LC Fiber Media Converter for 10/100/1000 Network - 550m - Gigabit Ethernet - 850nm - with SFP Transceiver (MCM110MMLC) - fibre media converter - 10Mb LAN, 100Mb LAN, 1GbE



03-10-2024

SKU	MCM110MMLC
Product Description:	StarTech.com Multimode (MM) LC Fiber Media Converter for 10/100/1000 Network - 550m - Gigabit Ethernet - 850nm - with SFP Transceiver (MCM110MMLC) - fibre media converter - 10Mb LAN, 100Mb LAN, 1GbE
Device Type:	Fibre media converter - RJ-45 / LC multi-mode
Form Factor:	External
Cabling Type:	10Base-T, 1000Base-LX, 1000Base-SX, 100Base-TX, 1000Base-T
Data Transfer Rate:	1 Gbps
Optical Wave Length:	850 nm
Data Link Protocol:	10Mb LAN, 100Mb LAN, 1GbE

General

Device Type: Fibre media converter

Form Factor: External

Colour: Brown

Networking

Connectivity Technology: Wired

Cabling Type: 10Base-T, 1000Base-LX, 1000Base-SX, 100Base-TX, 1000Base-T

Data Link Protocol: 10Mb LAN, 100Mb LAN, 1GbE

Data Transfer Rate: 1 Gbps

Optical Wave Length: 850 nm

Max Transfer Distance: 550 m

Features: Auto-negotiation, auto-uplink (auto MDI/MDI-X), Link Fault Pass Through function (LFP), Jumbo Frames support, metal housing

Compliant Standards: IEEE 802.3, IEEE 802.3u, IEEE 802.3z, IEEE 802.3ab

Compatibility Information

Designed For: P/N: SVA5N3NEUA

Environmental Parameters

Min Operating Temperature: 0 °C

Max Operating Temperature: 50 °C

Humidity Range Operating: 5 - 95% (non-condensing)

Manufacturer Warranty

Service & Support: Limited warranty - 2 years

Dimensions & Weight

Width: 7 cm

Depth: 2.6 cm

Height: 9.7 cm

Weight: 200 g

Power

Power Device: External power adapter

Voltage Required: AC 120/230 V

Power Consumption Operational: 5 Watt

Miscellaneous

MTBF: 50,000 hours

Compliant Standards: FCC, RoHS, MSA

Expansion / Connectivity

Interfaces: 1 x Ethernet 10Base-T/100Base-TX/1000Base-T - RJ-45 female ; 1 x Ethernet 1000Base-LX/1000Base-SX - LC multi-mode female x 2