


# StarTech.com Multimode (MM) LC Fiber Media Converter for 1Gbe Network - 550m Range - Gigabit Ethernet - 850nm - with SFP Transceiver (ET91000LC2) - fibre media converter - 1GbE



Not in stock

|                      |                                                                                                                                                                                  |
|----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| SKU                  | ET91000LC2                                                                                                                                                                       |
| Product Description: | StarTech.com Multimode (MM) LC Fiber Media Converter for 1Gbe Network - 550m Range - Gigabit Ethernet - 850nm - with SFP Transceiver (ET91000LC2) - fibre media converter - 1GbE |
| Device Type:         | Fibre media converter - RJ-45 / LC multi-mode                                                                                                                                    |
| Form Factor:         | External                                                                                                                                                                         |
| Localisation:        | North America, United Kingdom, Europe                                                                                                                                            |
| Cabling Type:        | 1000Base-LX, 1000Base-SX, 1000Base-T                                                                                                                                             |
| Data Transfer Rate:  | 1 Gbps                                                                                                                                                                           |
| Optical Wave Length: | 850 nm                                                                                                                                                                           |



## General

|               |                                       |
|---------------|---------------------------------------|
| Device Type:  | Fibre media converter                 |
| Form Factor:  | External                              |
| Colour:       | Black                                 |
| Localisation: | North America, United Kingdom, Europe |

## Networking

|                          |                                                                          |
|--------------------------|--------------------------------------------------------------------------|
| Connectivity Technology: | Wired                                                                    |
| Cabling Type:            | 1000Base-LX, 1000Base-SX, 1000Base-T                                     |
| Data Link Protocol:      | 1GbE                                                                     |
| Data Transfer Rate:      | 1 Gbps                                                                   |
| Optical Wave Length:     | 850 nm                                                                   |
| Max Transfer Distance:   | 550 m                                                                    |
| Features:                | Auto-uplink (auto MDI/MDI-X), half duplex mode, full duplex mode, rugged |

## Compatibility Information

|               |                                      |
|---------------|--------------------------------------|
| Designed For: | P/N: ETCHS2U, SVA12M2NEUA, SVA12M5NA |
|---------------|--------------------------------------|

## Environmental Parameters

|                            |          |
|----------------------------|----------|
| Min Operating Temperature: | 0 °C     |
| Max Operating Temperature: | 60 °C    |
| Humidity Range Operating:  | 10 - 90% |

## Manufacturer Warranty

|                    |                            |
|--------------------|----------------------------|
| Service & Support: | Limited warranty - 2 years |
|--------------------|----------------------------|

## Dimensions & Weight

|         |         |
|---------|---------|
| Width:  | 9.5 cm  |
| Depth:  | 16 cm   |
| Height: | 2 cm    |
| Weight: | 0.62 kg |

## Power

|                   |                        |
|-------------------|------------------------|
| Power Device:     | External power adapter |
| Voltage Required: | AC 120/230 V           |

## Miscellaneous

|                      |                          |
|----------------------|--------------------------|
| MTBF:                | 65,000 hours             |
| Compliant Standards: | Plug and Play, FCC, RoHS |

## Expansion / Connectivity

|             |                                                                                                          |
|-------------|----------------------------------------------------------------------------------------------------------|
| Interfaces: | 1 x Ethernet 1000Base-T - RJ-45 female   1 x Ethernet 1000Base-LX/1000Base-SX - LC multi-mode female x 2 |
|-------------|----------------------------------------------------------------------------------------------------------|

