

StarTech.com Singlemode (SM) SC Fiber Media Converter for 10/100/1000 Network, 10km, Gigabit Ethernet, 1310nm, w/ Auto Negotiation, Gigabit Ethernet to Single Mode (SMF) SC Fiber Converter - Ethernet Over Fiber (MCMGBSCSM10) - fibre media converter - 10Mb



In Stock(16)

SKU	MCMGBSCSM10
Product Description:	StarTech.com Singlemode (SM) SC Fiber Media Converter for 10/100/1000 Network, 10km, Gigabit Ethernet, 1310nm, w/ Auto Negotiation, Gigabit Ethernet to Single Mode (SMF) SC Fiber Converter - Ethernet Over Fiber (MCMGBSCSM10) - fibre media converter - 10Mb LAN, 100Mb LAN, 1GbE
Device Type:	Fibre media converter - RJ-45 / SC single-mode
Form Factor:	External
Cabling Type:	1000Base-LX, 100Base-TX, 1000Base-T
Data Transfer Rate:	1 Gbps
Optical Wave Length:	1310 nm
Data Link Protocol:	10Mb LAN, 100Mb LAN, 1GbE



General

Device Type:	Fibre media converter
Form Factor:	External

Networking

Connectivity Technology:	Wired
Cabling Type:	1000Base-LX, 100Base-TX, 1000Base-T
Data Link Protocol:	10Mb LAN, 100Mb LAN, 1GbE
Data Transfer Rate:	1 Gbps
Optical Wave Length:	1310 nm
Max Transfer Distance:	10 km
Status Indicators:	Port duplex mode, power, link/activity
Features:	Auto-uplink (auto MDI/MDI-X), full duplex mode, surge protection, 9 KB Jumbo Frame
Compliant Standards:	IEEE 802.3, IEEE 802.3u, IEEE 802.1Q, IEEE 802.3ab, IEEE 802.3x

Environmental Parameters

Min Operating Temperature:	0 °C
Max Operating Temperature:	50 °C
Humidity Range Operating:	5 - 90%

Manufacturer Warranty

Service & Support:	Limited warranty - 2 years
--------------------	----------------------------

Dimensions & Weight

Width:	7 cm
Depth:	9.7 cm
Height:	2.6 cm
Weight:	200 g

Power

Power Device:	External power adapter
Voltage Required:	AC 100 - 240 V
Power Consumption Operational:	5 Watt

Miscellaneous

MTBF:	50,000 hours
Compliant Standards:	cUL, FCC, RoHS, WEEE

Expansion / Connectivity

Interfaces:	1 x Ethernet 100Base-TX/1000Base-T - RJ-45 female 1 x Ethernet 1000Base-LX - SC single-mode female x 2
-------------	--

