

StarTech.com USB 3.0 Ethernet Adapter - USB 3.0 Network Adapter NIC with USB Port - USB to RJ45 - USB Passthrough (USB31000SPTB) - network adapter - USB 3.0 - Gigabit Ethernet



In Stock(46)

SKU	USB31000SPTB
Product Description:	StarTech.com USB 3.0 Ethernet Adapter - USB 3.0 Network Adapter NIC with USB Port - USB to RJ45 - USB Passthrough (USB31000SPTB) - network adapter - USB 3.0 - Gigabit Ethernet
Device Type:	Network adapter
Form Factor:	External
Interface (Bus) Type:	SuperSpeed USB 3.0
Ports:	Gigabit Ethernet
Dimensions (WxDxH):	3.5 cm x 8.2 cm x 1.7 cm
Weight:	50 g

General

Device Type:	Network adapter
Form Factor:	External
Interface (Bus) Type:	SuperSpeed USB 3.0

Networking

Ports:	Gigabit Ethernet
--------	------------------

Connectivity Technology:	Wired
--------------------------	-------

Cabling Type:	Ethernet 10Base-T, Ethernet 100Base-TX, Ethernet 1000Base-T
---------------	---

Data Link Protocol:	Ethernet, Fast Ethernet, Gigabit Ethernet
---------------------	---

Status Indicators:	Port transmission speed, link/activity
--------------------	--

Features:	Flow control, full duplex capability, auto-uplink (auto MDI/MDI-X), USB powered, IPv4 and IPv6 Large Send Offload and Checksum Offload (LSO/TCO), Jumbo Frames support, VLAN Tagging (not supported in MacOS)
-----------	---

Compliant Standards:	IEEE 802.3, IEEE 802.3u, IEEE 802.3i, IEEE 802.1Q, IEEE 802.3ab, IEEE 802.3x
----------------------	--

Processor / Memory

Processor:	ASIX AX88179
------------	--------------

Expansion / Connectivity

Interfaces:	1 x 1000Base-T - RJ-45 - female 1 x USB 3.0 - 9 pin USB Type A - female
-------------	---

Miscellaneous

Cables Included:	1 x USB cable (integrated) - 15.24 cm
------------------	---------------------------------------

Compliant Standards:	FCC, RoHS
----------------------	-----------

Colour:	Black
---------	-------

Compatibility Information

Designed For:	P/N: TB33A1C
---------------	--------------

Environmental Parameters

Min Operating Temperature:	0 °C
----------------------------	------

Max Operating Temperature:	50 °C
----------------------------	-------

Humidity Range Operating:	5 - 85%
---------------------------	---------

Manufacturer Warranty

Service & Support:	Limited warranty - 2 years
--------------------	----------------------------

Dimensions & Weight

Width:	3.5 cm
--------	--------

Depth:	8.2 cm
--------	--------

Height:	1.7 cm
---------	--------

Weight:	50 g
---------	------

Software / System Requirements

Software Included:	Drivers & Utilities
--------------------	---------------------

OS Required:	Microsoft Windows Server 2003, Microsoft Windows Server 2008 R2, Microsoft Windows Server 2012, Microsoft Windows Server 2012 R2, Microsoft Windows Server 2016, Linux Kernel 2.6.25 or later, Google Chrome OS 55 or later, Microsoft Windows Server 2019, Linux LTS versions only, Apple MacOS X 10.6 - 10.15, Microsoft Windows XP / Vista / 7 / 8 / 8.1 / 10 / 11, Apple macOS 11.3 or later
--------------	--