

StarTech.com USB C Multiport Adapter - Portable USB-C Dock to 4K HDMI, 2-pt USB 3.0 Hub, SD/SDHC, GbE, 60W PD Pass-Through - USB Type-C/Thunderbolt 3 - NEW VERSION AVAILABLE DKT30CSDHPD3 (DKT30CSDHPD) - docking station - USB-C / Thunderbolt 3 - 1GbE



In Stock(41)

SKU	DKT30CSDHPD
Product Description:	StarTech.com USB C Multiport Adapter - Portable USB-C Dock to 4K HDMI, 2-pt USB 3.0 Hub, SD/SDHC, GbE, 60W PD Pass-Through - USB Type-C/Thunderbolt 3 - NEW VERSION AVAILABLE DKT30CSDHPD3 (DKT30CSDHPD) - docking station - USB-C / Thunderbolt 3 - 1GbE
Product Type:	Docking station
Docking Interface:	USB-C / Thunderbolt 3
Dimensions (WxDxH):	4.6 cm x 11.6 cm x 1.6 cm
Weight:	86 g
Colour:	Grey, black
Networking:	Gigabit Ethernet

General

Product Type:	Docking station
Width:	4.6 cm
Depth:	11.6 cm
Height:	1.6 cm
Weight:	86 g
Enclosure Colour:	Grey, black

Networking

Data Link Protocol:	Gigabit Ethernet
Compliant Standards:	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, USB 1.1, USB 2.0, USB 3.0

Expansion / Connectivity

Expansion Slots:	1 (total) / 1 (free) x SD / MMC Memory Card
Interfaces:	2 x SuperSpeed USB 3.0 - 9 pin USB Type A 1 x USB-C - 24 pin USB-C (power only) Video - HDMI input - 19 pin HDMI Type A 1 x network - 10Base-T/100Base-TX/1000Base-T - RJ-45

Compatibility Information

Designed For:	P/N: ARMCBCL, ARMPIVOT, ARMPIVOTB, ARMPIVOTE, ARMPIVOTE2, ARMPIVOTHD, ARMPIVOTV2, ARMPIVSTND, ARMSLIM, ARMUNONB, ARMUNONB1, FPPNEUSTND, LTRISERP, MONSTADJD, MONSTADJDL
---------------	---

Environmental Parameters

Min Operating Temperature:	0 °C
Max Operating Temperature:	55 °C

Manufacturer Warranty

Service & Support:	Limited warranty - 3 years
--------------------	----------------------------

System Requirements

OS Required:	Google Chrome OS, Apple MacOS X 10.11 - 10.15, Apple macOS 11.0, Microsoft Windows 7 / 8 / 8.1 / 10 / 11, Apple macOS 12.0, Apple macOS 13.0
--------------	--

Miscellaneous

Cables Included:	1 x USB-C cable - 15.2 cm
Features:	USB powered, full duplex support
Compliant Standards:	FCC, RoHS, WEEE, RCM, UASP (USB Attached SCSI Protocol)

