

TP-Link Archer C20 AC750 - wireless router - Wi-Fi 5 - desktop



13-05-2024

SKU	Archer C20
Product Description:	TP-Link Archer C20 AC750 - wireless router - Wi-Fi 5 - desktop
Device Type:	Wireless router - 4-port switch (integrated)
Enclosure Type:	Desktop
WAN Ports Qty:	1
Data Link Protocol:	Ethernet, Fast Ethernet, IEEE 802.11b, IEEE 802.11a, IEEE 802.11g, IEEE 802.11n, IEEE 802.11ac
Frequency Band:	2.4 GHz / 5 GHz
Data Transfer Rate:	733 Mbps

General

Device Type:	Wireless router - 4-port switch (integrated)
Enclosure Type:	Desktop
Connectivity Technology:	Wireless, wired
Data Link Protocol:	Ethernet, Fast Ethernet, IEEE 802.11b, IEEE 802.11a, IEEE 802.11g, IEEE 802.11n, IEEE 802.11ac
Frequency Band:	2.4 GHz / 5 GHz
Data Transfer Rate:	733 Mbps
Performance:	Maximum data rate (2.4 GHz): 300 Mbps ; Maximum data rate (5 GHz): 433 Mbps
Network / Transport Protocol:	PPTP, L2TP, IPSec, DDNS
Encryption Algorithm:	128-bit WEP, 64-bit WEP, WPA, WPA2, WPA-PSK, WPA2-PSK
Wi-Fi Rating:	AC750

Environmental Parameters

Min Operating Temperature:	0 °C
Max Operating Temperature:	40 °C
Humidity Range Operating:	10 - 90% (non-condensing)

Manufacturer Warranty

Service & Support:	Limited warranty - 3 years
--------------------	----------------------------

Dimensions & Weight (Shipping)

Shipping Width:	28.5 cm
Shipping Depth:	22.3 cm
Shipping Height:	9.1 cm

Dimensions & Weight

Width:	23 cm
Depth:	14.4 cm
Height:	3.5 cm

Software / System Requirements

General

Features:

Firewall protection, DMZ port, SPI, print server, MAC address filtering, IPv6 support, WDS support, IP address filtering, domain blocking, WMM support, QoS, virtual server support, WPS, FTP server, port forwarding, bandwidth control, IPv4 support, port triggering

Compliant Standards:

IEEE 802.11b, IEEE 802.11a, IEEE 802.11g, IEEE 802.11n, UPnP, IEEE 802.11ac, FCC, RoHS

Software / System Requirements

Software Included:	Drivers & Utilities
OS Required:	Apple MacOS, Linux, Microsoft Windows Vista / XP / 7 / 8 / 8.1

Miscellaneous

Cables Included:	1 x network cable
------------------	-------------------

Power

Power Device:	External power adapter
---------------	------------------------

Aerial

Aerial:	External integrated
Antenna Qty:	3
Directivity:	Omni-directional

Expansion / Connectivity

Interfaces:	LAN: 4 x 10Base-T/100Base-TX - RJ-45 ; WAN: 1 x 10Base-T/100Base-TX - RJ-45
-------------	--

