

TP-Link LiteWave LS1005G - switch - 5 ports - unmanaged



In Stock(10)

SKU	LS1005G
Product Description:	TP-Link LiteWave LS1005G - switch - 5 ports - unmanaged
Device Type:	Switch - 5 ports - unmanaged
Subtype:	Gigabit Ethernet
Ports:	5 x 10/100/1000
Performance:	Switching capacity: 10 Gbps Forwarding performance: 7.4 Mpps
MAC Address Table Size:	2K entries
Jumbo Frame Support:	16KB



General

Device Type: Switch - 5 ports - unmanaged

Enclosure Type: Desktop, wall-mountable

Subtype: Gigabit Ethernet

Ports: 5 x 10/100/1000

Performance: Switching capacity: 10 Gbps | Forwarding performance: 7.4 Mpps

MAC Address Table Size: 2K entries

Jumbo Frame Support: 16KB

Features: Flow control, auto-negotiation, auto-uplink (auto MDI/MDI-X), store and forward, plastic housing, fanless, Green Technology

Compliant Standards: IEEE 802.3u, IEEE 802.3i, IEEE 802.3ab, IEEE 802.3x

Status Indicators: Power, link/activity

Environmental Parameters

Min Operating Temperature: 0 °C

Max Operating Temperature: 40 °C

Humidity Range Operating: 10 - 90% (non-condensing)

Min Storage Temperature: -40 °C

Max Storage Temperature: 70 °C

Humidity Range Storage: 5 - 90% (non-condensing)

Dimensions & Weight

Width: 9 cm

Depth: 7.2 cm

Height: 2.3 cm

Miscellaneous

Compliant Standards: FCC, RoHS

Power

Power Device: External power adapter

Power Consumption Operational: 3.7 Watt

Expansion / Connectivity

Interfaces: 5 x 1000Base-T RJ-45

