


TP-Link TL-PA8010P KIT - Starter Kit - powerline adapter - wall-pluggable



SKU	TL-PA8010P KIT
Product Description:	TP-Link TL-PA8010P KIT - Starter Kit - powerline adapter - wall-pluggable
Device Type:	Powerline adapter
Enclosure Type:	Wall-pluggable
Data Link Protocol:	Ethernet, Fast Ethernet, Gigabit Ethernet, HomePlug AV (HPAV), HomePlug AV (HPAV) 2.0
Data Transfer Rate:	1.2 Gbps
Features:	2T2R MIMO technology
Compliant Standards:	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, HomePlug AV, HomePlug AV 2.0, IEEE 1901



General

Device Type: Powerline adapter

Enclosure Type: Wall-pluggable

Connectivity Technology: Wired

Data Link Protocol: Ethernet, Fast Ethernet, Gigabit Ethernet, HomePlug AV (HPAV), HomePlug AV (HPAV) 2.0

Data Transfer Rate: 1.2 Gbps

Max Range Indoors: 300 m

Encryption Algorithm: 128-bit AES

Features: 2T2R MIMO technology

Compliant Standards: IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, HomePlug AV, HomePlug AV 2.0, IEEE 1901, Plug and Play, RoHS

Status Indicators: Power, link/activity

Line Properties

Line Coding Format: OFDM

Environmental Parameters

Min Operating Temperature: 0 °C

Max Operating Temperature: 40 °C

Humidity Range Operating: 10 - 90% (non-condensing)

Dimensions & Weight

Width: 13.1 cm

Depth: 7.2 cm

Height: 4.2 cm

Software / System Requirements

Software Included: Drivers & Utilities

OS Required: Apple MacOS, Linux, Microsoft Windows Server 2003, Microsoft Windows 2000/XP/Vista/7, Windows 8

Miscellaneous

Cables Included: 1 x network cable - 2 m

Localisation: United Kingdom, Europe

Power

Power Device: Internal power supply

Voltage Required: AC 220 V (50 Hz)

Power Consumption Operational: 6 Watt

Expansion / Connectivity

Interfaces: LAN: 1 x HomePlug AV ; LAN: 1 x 10Base-T/100Base-TX/1000Base-T - RJ-45

