

VivoLink - conference camera



In Stock(10)

SKU	VLCAM100
Product Description:	VivoLink - conference camera
Device Type:	Conference camera - pan / tilt / zoom - indoor
Audio:	Yes: built-in two microphones
Dimensions (WxDxH):	22.2 cm x 5.65 cm x 9.325 cm
Weight:	530 g
Connectivity Technology:	Wired
Camera:	Colour



General

Device Type:	Conference camera
Audio Support:	Yes: built-in two microphones
Connectivity Technology:	Wired
Width:	22.2 cm
Depth:	5.65 cm
Height:	9.325 cm
Weight:	530 g

Camera

Type:	Colour - pan / tilt / zoom - indoor
Digital Video Format:	MJPEG, H.264, YUY2, H.265
Max Digital Video Resolution:	3840 x 2160
Video Modes:	720p, 1080p, 4K
Digital Zoom:	4
Minimum Illumination:	0.1 lux F1.8 - AGC on
Digital Video Capture Resolution:	1280 x 720, 640 x 480, 1920 x 1080
Frame Rate (max):	30 frames per second
Features:	ePTZ, 3D digital noise reduction (DNR), 2D digital noise reduction (DNR)

Environmental Parameters

Min Operating Temperature:	-10 °C
Max Operating Temperature:	50 °C
Relative Humidity (operating):	20 - 80%

Software / System Requirements

OS Required:	Microsoft Windows 7 / 8 / 10, Apple MacOS X 10.10 or later
--------------	--

Power

Power Device:	5 Watt
---------------	--------

Miscellaneous

Included Accessories:	Remote control
Cables Included:	1 x SuperSpeed USB cable

Expansion / Connectivity

Ports:	USB 3.0
--------	---------

Interfaces

Computer Interface:	USB 3.0
---------------------	---------

Lens Construction

Focal Length:	2.72 mm
Lens Iris:	F/2.5
Vertical Field of View (degree):	120

Image Sensor

Type:	8.28 MP CMOS 1/2.5"
-------	---------------------

