

Yealink CS10 - IP speaker - for conference system



29-10-2024

SKU	1303094
Product Description:	Yealink CS10 - IP speaker - for conference system
Product Type:	IP speaker - for conference system
Speaker Type:	Coaxial - 2-way - active
Continuous Power:	20 Watt
Nominal Impedance:	8 Ohm
Amplifier:	Integrated
Colour:	White



General

Product Type: IP speaker - for conference system

Enclosure Colour: White

Enclosure Material: Aluminium alloy, fibreglass-reinforced polyamide, ABS polycarbonate

Design Features: Paintable grille

Grille Colour: White

Speaker System

Speaker Type: Coaxial - 2-way - active

Continuous Power: 20 Watt

Frequency Response (-6dB): 100 - 20000 Hz

Nominal Impedance: 8 Ohm

Max Output Level (Max SPL): 99 dB

Sensitivity: 88 dB (1W@1m)

Amplifier: Integrated

Coverage: 120°

Recommended Placing: Ceiling mountable

Detachable Grilles: Yes

Speaker System Details

Driver Details: Speaker: woofer driver - 5.7" | Speaker: tweeter driver - 1.1"

Environmental Parameters

Min Operating Temperature: 0 °C

Max Operating Temperature: 50 °C

Min Storage Temperature: 0 °C

Max Storage Temperature: 50 °C

Humidity Range Operating: 5 - 90%

Dimensions & Weight

Diameter: 28.72 cm

Depth: 12.5 cm

Weight: 2.808 kg

Dimensions (WxDxH) / Weight Details: Cover: / 207 g

Power

Power Source: Power over Ethernet (PoE)

Miscellaneous

Included Accessories: Magnetic speaker grille, mounting bracket, dust cover, screws

Compliant Standards: UL 2043, IEEE 802.3at, PoE+

Connections

Connector Type: Network (RJ-45)

