

Symbol LS2208 - barcode scanner



17-06-2024

SKU	LS2208-1AZR0100ER
Product Description:	Symbol LS2208 - barcode scanner
Type:	Barcode scanner - handheld - RS-232 - decoded
Colour:	Cash register white
Localisation:	EMEA
Minimum Bar Width:	5 mil
Scan Element Type:	Visible laser diode
Scan Speed:	100 scan / sec

General

Type:	Barcode scanner - handheld
Colour:	Cash register white
Localisation:	EMEA

Environmental Parameters

Min Operating Temperature:	0 °C
Max Operating Temperature:	50 °C
Humidity Range Operating:	5 - 95% (non-condensing)
Drop Specification:	1.5 m to concrete

Manufacturer Warranty

Service & Support:	Limited warranty - 5 years
--------------------	----------------------------

Dimensions & Weight

Width:	6.3 cm
Depth:	8.4 cm
Height:	15.2 cm
Weight:	146 g

Power

Power Device:	Power adapter
Electric Current Required:	130 mA (typical), 175 mA (peak)

Miscellaneous

Included Accessories:	Stand
-----------------------	-------

Miscellaneous

Cables Included:	1 x serial cable - external
Compliant Standards:	Plug and Play, VCCI, EN 60950, IEC950, UL 1950, ICES-003 Class B, FCC Part 15 B, MITI, EMC, RoHS, UL 60950-1, IEC 60950-1, EN 60950-1, CSA C22.2 No. 950, IEC 60825-1, CSA C22.2 No. 60950-1, EN 60825-1

Expansion / Connectivity

Interfaces:	1 x RS-232 - DB-9
-------------	-------------------

Barcode

Interface Type:	RS-232
Minimum Bar Width:	5 mil
Scan Element Type:	Visible laser diode
Light Source Wave Length:	650 nm
Scan Mode:	Single-pass
Scan Speed:	100 scan / sec
Max Working Distance:	76 cm
Skew (Degrees):	60
Pitch (Degrees):	65
Print Contrast Signal (PCS):	20%
Decode Capability:	Code 93, Code 39, UCC/EAN-128, IATA, GS1 DataBar, Code 39 Full ASCII, Discrete 2 of 5, Codabar, Code 128, Code 11, UPC, Interleaved 2 of 5, MSI-Plessey, Code 128 Full ASCII, Code 39 Trioptic
TTL Decoding:	Decoded

Barcode

Connectivity Technology: Wired

OK Notification: Beeper, LED indicator

Features: Triggered, Advanced Data Formatting (ADF)

