

# Zebra DS2208 - barcode scanner



In Stock(1092)

|                      |                                                                 |
|----------------------|-----------------------------------------------------------------|
| SKU                  | DS2208-SR00007ZZWW                                              |
| Product Description: | Zebra DS2208 - barcode scanner                                  |
| Type:                | Barcode scanner - handheld - interface cable required - decoded |
| Colour:              | Twilight black                                                  |
| Minimum Bar Width:   | 4 mil                                                           |
| Scan Element Type:   | 2D imager                                                       |
| Sensor Resolution:   | 640 x 480                                                       |
| Scan Speed:          | 762 mm / sec                                                    |

## General

|         |                            |
|---------|----------------------------|
| Type:   | Barcode scanner - handheld |
| Colour: | Twilight black             |

## Environmental Parameters

|                            |                          |
|----------------------------|--------------------------|
| Min Operating Temperature: | 0 °C                     |
| Max Operating Temperature: | 50 °C                    |
| Humidity Range Operating:  | 5 - 95% (non-condensing) |
| Drop Specification:        | 1.5 m to concrete        |

## Manufacturer Warranty

|                    |                            |
|--------------------|----------------------------|
| Service & Support: | Limited warranty - 5 years |
|--------------------|----------------------------|

## Dimensions & Weight

|         |         |
|---------|---------|
| Width:  | 6.6 cm  |
| Depth:  | 9.9 cm  |
| Height: | 16.5 cm |
| Weight: | 161.6 g |

## Miscellaneous



## Miscellaneous

|                      |                                                                                                                                                                                                                                              |
|----------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Compliant Standards: | UL, VDE, EN 61000-6-2, RoHS, UL 60950-1 Second Edition, CAN/CSA C22.2 No. 60950-1-07, IP42, EN 61000-3-2:2006+A1:2009+A2:2009, IEC 60601-1-2:2007, EN 50581:2012, ICES-003 issue 5                                                           |
|                      | Class B, IEC 62471:2006, EN 62471:2008, EN 60601-1-2:2007, EN 60950-1:2006+A11:2009+A1:2010+A12:2011+AC:2011, EN 61000-3-3:2013, EN 55024:2010, EN 55022:2010/AC:2011, IEC 60950-1:2005 + A1:2009 + A2:2013, CU, FCC CFR47 Part 15 B Class B |

## Barcode

|                              |                                                                                                                                                                                                                      |
|------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Interface Type:              | Interface cable required                                                                                                                                                                                             |
| Minimum Bar Width:           | 4 mil                                                                                                                                                                                                                |
| Scan Element Type:           | 2D imager                                                                                                                                                                                                            |
| Sensor Resolution:           | 640 x 480                                                                                                                                                                                                            |
| Light Source Wave Length:    | 645 nm                                                                                                                                                                                                               |
| Scan Mode:                   | Single-pass                                                                                                                                                                                                          |
| Scan Speed:                  | 762 mm / sec                                                                                                                                                                                                         |
| Max Working Distance:        | 36.8 cm                                                                                                                                                                                                              |
| Skew (Degrees):              | 65                                                                                                                                                                                                                   |
| Pitch (Degrees):             | 65                                                                                                                                                                                                                   |
| Print Contrast Signal (PCS): | 25%                                                                                                                                                                                                                  |
| Decode Capability:           | Code 93, Industrial 2 of 5, Code 39, NW-7, GS1 DataBar, QR code, MaxiCode, Aztec code, Italy Pharmacode, Codabar, Code 128, Code 11, UPC, PDF417, MSI-Plessey, Data Matrix, TLC39, Micro QR code, China Han Xin Code |

Barcode

TTL  
Decoding: Decoded

Connectivity  
Technology: Wired

OK  
Notification: Beeper, LED indicator

