

Zebra DS3678-ER - barcode scanner



In Stock(37)

SKU	DS3678-ER3U42A2SVW
Product Description:	Zebra DS3678-ER - barcode scanner
Type:	Barcode scanner - portable - keyboard wedge, RS-232, USB, Bluetooth 4.0 - decoded
Colour:	Industrial green
Minimum Bar Width:	3 mil
Scan Element Type:	2D imager
Connectivity Technology:	Wireless, wired
Wireless Connectivity:	Bluetooth 4.0 LE

General

Type:	Barcode scanner - portable
Colour:	Industrial green

Barcode

Interface Type:	Keyboard wedge, RS-232, USB, Bluetooth 4.0
Minimum Bar Width:	3 mil
Scan Element Type:	2D imager
Scan Mode:	Single-pass
Skew (Degrees):	60
Pitch (Degrees):	60
Decode Capability:	GS1 DataBar, QR code, MaxiCode, Aztec code, MicroPDF417, PDF417, Data Matrix, TLC39, Micro QR code, China Han Xin Code
TTL Decoding:	Decoded
Connectivity Technology:	Wireless, wired

Environmental Parameters

Min Operating Temperature:	-20 °C
Max Operating Temperature:	50 °C
Humidity Range Operating:	5 - 95% (non-condensing)
Drop Specification:	2.4 m to concrete

Manufacturer Warranty

Service & Support:	Limited warranty - 3 years
--------------------	----------------------------

Dimensions & Weight

Width:	7.7 cm
Depth:	14.3 cm
Height:	18.5 cm
Weight:	436 g

Power

Power Device:	Power adapter
Battery:	1 x Lithium Ion

Miscellaneous

Included Accessories:	Cradle
-----------------------	--------

Barcode

OK
Notification: Beeper, LED indicator, vibration

Features: Rugged

Networking

Wireless Connectivity: Bluetooth 4.0 LE

Miscellaneous

Cables
Included: 1 x USB cable - external

UL, VDE, EN 61000-6-2, RoHS, UL 60950-1
Second Edition, IP67, CAN/CSA C22.2 No.
60950-1-07, EN 61000-3-
2:2006+A1:2009+A2:2009, IEC 60601-1-
2:2007, EN 50581:2012, ICES-003 issue 5
Compliant Class B, IEC 62471:2006, EN 62471:2008, EN
Standards: 60601-1-2:2007, EN 60950-
1:2006+A11:2009+A1:2010+A12:2011+AC:2011,
EN 61000-3-3:2013, EN 55024:2010, EN
55022:2010/AC:2011, IEC 60950-1:2005 +
A1:2009 + A2:2013, CU, FCC CFR47 Part 15 B
Class B

Expansion / Connectivity

Interfaces: 1 x USB | 1 x keyboard wedge | 1 x RS-232

