

Zebra LI2208 - barcode scanner



Not in stock

SKU	LI2208-SR00007ZZWW
Product Description:	Zebra LI2208 - barcode scanner
Type:	Barcode scanner - handheld - decoded
Colour:	Twilight black
Minimum Bar Width:	3 mil
Scan Field Width:	2.5 cm - 78.7 cm
Scan Element Type:	Linear imager
Scan Speed:	547 scan / sec

General

Type:	Barcode scanner - handheld
Colour:	Twilight black

Environmental Parameters

Min Operating Temperature:	0 °C
Max Operating Temperature:	50 °C
Humidity Range Operating:	5 - 95% (non-condensing)
Drop Specification:	1.8 m to concrete

Manufacturer Warranty

Service & Support:	Limited warranty - 5 years
--------------------	----------------------------

Dimensions & Weight

Width:	9.9 cm
Depth:	16 cm
Height:	6.7 cm
Weight:	140 g

Software

Software Included:	Drivers & Utilities
--------------------	---------------------

Power

Power Device:	No power supply
Electric Current Required:	40 mA (standby), 165 mA (operating)

Miscellaneous

Miscellaneous

Cables

Included: 1 x no data cable is included

Compliant Standards:

IEC 60601-1-2, ICES-003 Class B, FCC Part 15 B, RoHS, UL 60950-1, IEC 60950-1, EN 60950-1, CSA C22.2 No. 60950-1, IP42

Barcode

Minimum Bar Width:

3 mil

Scan Field Width:

2.5 cm - 78.7 cm

Scan Element Type:

Linear imager

Light Source Wave Length:

617 nm

Scan Mode:

Single-pass

Scan Speed:

547 scan / sec

Max Working Distance:

6 m

Skew (Degrees):

65

Pitch (Degrees):

65

Print Contrast Signal (PCS):

15%

Decode Capability:

EAN/JAN, Code 93, Matrix 2 of 5, Code 39, UCC/EAN-128, ISBT 128, NW-7, ISBN, GS1 DataBar, Bookland, Code 32, Code 39 Full ASCII, EAN/JAN-8, EAN/JAN-13, UPC-A, UPC-E, Discrete 2 of 5, Italy Pharmacode, Codabar, Code 128, Code 11, UPC, Interleaved 2 of 5, ITF, IATA 2 of 5, UPC-E1, GS1 DataBar-14, Code 39 Trioptic, GS1 DataBar Expanded, GS1 DataBar Limited

TTL Decoding:

Decoded

Connectivity Technology:

Wired

e