

Zebra ZT230 - label printer - B/W - direct thermal / thermal transfer



19-06-2024

SKU	ZT23042-T0E200FZ
Product Description:	Zebra ZT230 - label printer - B/W - direct thermal / thermal transfer
Printer Type:	Label printer - direct thermal / thermal transfer - B/W
Weight:	9.1 kg
Localisation:	United Kingdom, Europe
Max Media Size:	Roll (11.4 cm)
Min Media Size (Custom):	19.4 mm
Max Media Size (Custom):	114 mm x 991 mm

General

Printer Type:	Label printer - direct thermal / thermal transfer - monochrome
Localisation:	United Kingdom, Europe

Printer

Print Speed:	Up to 152 mm/sec - B/W - 203 dpi - Roll (11.4 cm)
Built-in Devices:	Status LCD
Connectivity Technology:	Wired
Interface:	USB, LAN, serial
Max Resolution (B&W):	203 dpi
Language Simulation:	ZPL, ZPL II, EPL, Extensible Mark-up Language (XML)
Fonts Included:	1 x scalable 7 x bitmapped

Dimensions & Weight (Shipping)

Weight (Shipping):	11.4 kg
--------------------	---------

Dimensions & Weight

Width:	24.2 cm
Depth:	43.2 cm
Height:	27.7 cm
Weight:	9.1 kg

Environmental Parameters

Min Operating Temperature:	5 °C
Max Operating Temperature:	40 °C
Humidity Range Operating:	20 - 85% (non-condensing)

Manufacturer Warranty

Service & Support:	Limited warranty - 1 year
--------------------	---------------------------

Environmental Standards

ENERGY STAR:	Yes
--------------	-----

Power

Printer

Barcodes:	Code 93, Industrial 2 of 5, Code 39, Code 49, CODABLOCK, ISBT 128, QR code, MaxiCode, Aztec code, LOGMARS, EAN/JAN-8, EAN/JAN-13, UPC-A, UPC-E, MicroPDF417, Codabar, Code 11, Interleaved 2 of 5, Postnet, PDF417, Data Matrix, PLANET, TLC39, Plessey, Code 128B, Code 128C, Code 128A, Standard 2 of 5
Printer Features:	Zebra Programming Language (ZPL) support, XML-enabled printing, Multi-level Element Energy Equalizer (E3)

Processor

Processor:	400 MHz
------------	---------

RAM

RAM Installed (Max):	128 MB
Technology / Form Factor:	SDRAM

Flash Memory

Flash Memory:	128 MB
---------------	--------

Power

Power Device:	Power supply - internal
Frequency Required:	47 - 63 Hz

Miscellaneous

Compatible with Windows 7:	"Compatible with Windows 7" software and devices carry Microsoft's assurance that these products have passed tests for compatibility and reliability with 32-bit and 64-bit Windows 7.
Compliant Standards:	VCCI, C-Tick, BSMI, EN 61000-3-2, ICES-003, NOM, IEC 60950, EN 61000-3-3, EN55024, EN55022 Class B, FCC Part 15 B, CCC, KCC, GOST-R, S Mark, cTUVus, UkrSEPRO

Expansion / Connectivity

Connections:	1 x RS-232 - 9 pin D-Sub (DB-9) 1 x USB 1 x LAN
--------------	---

Networking

Networking:	Print server
Data Link Protocol:	Ethernet, Fast Ethernet

Media Handling

Media Type:	Labels, continuous paper labels, die cut labels
Max Media Size:	Roll (11.4 cm)
Min Media Size (Custom):	19.4 mm
Max Media Size (Custom):	114 mm x 991 mm
Media Sizes:	Roll (1.94 - 11.4 cm)
Max Printing Width:	104 mm
Max Printing Length:	3988 mm
Media Thickness Range:	0.076 mm - 0.25 mm
Roll Maximum Outer Diameter:	203 mm
Roll Core Diameter:	76 mm, 25 mm
Media Feeders:	1 x manual - 1 roll - Roll (11.4 cm)

