

Zyxel GS1200-8 - switch - 8 ports - Managed



In Stock(21)

SKU	GS1200-8-EU0101F
Product Description:	Zyxel GS1200-8 - switch - 8 ports - Managed
Device Type:	Switch - 8 ports - Managed
Subtype:	Gigabit Ethernet
Ports:	8 x 10/100/1000
Performance:	Switching capacity: 16 Gbps
Capacity:	Multicast groups: 128
MAC Address Table Size:	4K entries

General

Device Type:	Switch - 8 ports - Managed
Enclosure Type:	Desktop
Subtype:	Gigabit Ethernet
Ports:	8 x 10/100/1000
Performance:	Switching capacity: 16 Gbps
Capacity:	Multicast groups: 128
MAC Address Table Size:	4K entries
Jumbo Frame Support:	9KB
Routing Protocol:	IGMPv2, IGMP, IGMPv3
Remote Management Protocol:	HTTP

Features:	Flow control, VLAN support, auto-uplink (auto MDI/MDI-X), IGMP snooping, port mirroring, WRR queuing, Broadcast Storm Control, firmware upgradable, wall mountable, QoS, fanless, Energy Efficient Ethernet, loop prevention, 192KB packet buffer, CoS, tagged VLAN, metal housing, Link Aggregation, WRR, port-based QoS
-----------	---

Compliant Standards:	IEEE 802.3u, IEEE 802.3z, IEEE 802.1Q, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3x, IEEE 802.3az
----------------------	---

Environmental Parameters

Min Operating Temperature:	0 °C
Max Operating Temperature:	40 °C
Humidity Range Operating:	10 - 90% (non-condensing)
Min Storage Temperature:	-40 °C
Max Storage Temperature:	70 °C
Humidity Range Storage:	10 - 90% (non-condensing)

Dimensions & Weight (Shipping)

Shipping Width:	16.1 cm
Shipping Depth:	9 cm
Shipping Height:	9.5 cm
Shipping Weight:	497 g

Dimensions & Weight

Width:	15.5 cm
Depth:	8.5 cm
Height:	2.6 cm
Weight:	325 g

Miscellaneous

General

Status Indicators: Port status, port transmission speed, power

Miscellaneous

Compliant Standards: C-Tick, EMC, FCC, RoHS, EN 60950-1, LVD, EMC Class A, EMC Class B, BMSI

Localisation: Europe

Power

Power Device: External power adapter

Power Consumption Operational: 4.37 Watt

Expansion / Connectivity

Interfaces: 8 x 1000Base-T RJ-45

